



ECO FRIENDLY
SUSTAINABLE
BIODEGRADABLE



VBCI Series- A class of environmentally friendly corrosion inhibitors for a cleaner, greener, better tomorrow.

Vapro VBCI-844L

Sulphate-free Liquid VBCI Corrosion Inhibitor And Oxygen Scavenger

Passed German VIA (Vapour Inhibition Ability) Test TL 8135-002

NATO STOCK NUMBER: PENDING

Overview

Vapro VBCI-844L hailed as a technical breakthrough in corrosion control, it is a revolutionary corrosion inhibitor that inhibits ferrous metals against corrosion in seawater. Vapro VBCI-844L protects metals in sea water with salinity up to 35 0/00 and with chloride content up to 19,000 ppm. It eliminates the dependence of using fresh water for hydrotesting of storage tanks and piping systems. Vapro VBCI-844L also functions as an oxygen scavenger to reduce corrosion and pitting caused by dissolved oxygen in water. It is a sulphate-free product and effectively controls the propagation of corrosion causing sulphate reducing bacteria(SRB).

Hydrotest can now be carried out safely with sea water onboard ships, rigs, offshore equipment, pipes and storage tanks without experiencing the dire consequences of corrosion. Ballast tanks can now be protected without the need of using oil or solvent. Simply flood the ballast tank with sea water and add 550 to 700ppm of Vapro VBCI-844L by weight to the volume of sea water in the ballast tank.

Vapro VBCI-844L has found considerable application as a corrosion inhibitor in low concentrations and is effective in protecting ferrous metals against corrosion in sea water. It does not contain chromates or nitrites and is essentially non-toxic.



Advantages

- Effectively protects ferrous metals against corrosion in sea water with salinity up to 35 0/00 and with chloride up to 19,000 ppm.
- Free from Nitrites.
- Free from chromates.
- Eliminates the need of using fresh water for hydro testing without experiencing the dire consequences of corrosion.
- Low dosage.
- Essentially non-toxic.
- Economical.
- Does not contain ozone depleting substances.
- No other VCI corrosion inhibitor performs as effectively, reliably and consistently as Vapro VBCI-844L



Areas of Use

- Hydroblasting, hydrostatic testing.
- Tanks, casing, pumps, valves.
- Tubulars and piping systems exposed to sea water.
- Ballast tanks.
- Cooling system using sea water.

Procedure For Incorporating Vapro VBCI-844L With Hydrotest Water For Storage Tank

- Calculate the volume of the system to be hydrostatically pressure tested.
- Add Vapro VBCI-844L to sea water at a dosage of 550-700ppm by weight depending on the salinity of sea water.
- Agitate the mixture for even dispersion with vortex.
- Carry out pressure test.

Typical Properties

Form

Liquid

Appearance

Amber liquid

Solubility In Water

Yes

pH

8(1% solution)

Available Packaging

20 liters HPDE Pail or 200 liters HDPE drum



After 1500 hours
Mild steel immersed in sea
water with 700ppm of
Vapro VBCI-844L



After 1500 hours
Mild steel immersed in
sea water without
Vapro VBCI-844L

Magna

Magna International Pte Ltd

10H, Enterprise Road,
Singapore 629834.

Tel (65) 6786-2616

Fax (65) 6785-1497

Email info@magnachem.com.sg
info@vaprovci.com

Web <http://www.vaprovci.com>

Headquarters



Singapore

Regional Offices



Australia



Canada

Follow us on social media for
regular updates and news.



<https://www.facebook.com/vaprovci/>
<https://www.facebook.com/MagnaInternationalPteLtd/>

The details of our products are given completely free of undertaking. Since their application lies outside our control, we cannot accept any liability for the results. User shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.



Copyright 2018. Magna International Pte Ltd.

Magna, Vapro VCI and Vapro VBCI are registered trademarks of Magna International Pte Ltd.